



## Features:

### 32CH POE Face Detection 4K NVR with 4SATA

Support 32CH/12MP/8MP/6MP/5MP/4MP/3MP/1080P/1280×1024/960P/ 720P/960H/D1/CIF IPC  
Input H.265S/H.265+/H.265/H.264

Intuitive and user-friendly Graphic User Interface (GUI), Windows style operation by mouse

Multi-type recording: manual/timed/motion/sensor/POS/AI recording

Playback: 16CH simultaneous playback

Search: time slice, time, event, tag and smart search

Support face detection and comparison

Support multiple VCA (Video Content Analytics) events, such as object abandoned/missing, region intrusion, tripwire, video exception

Support license plate recognition

Support POS information overlay on live view and playback

Pentaplex: preview, record, playback, backup and remote access

DHCP, DDNS, PPPoE network protocol

Compatible with third-party IPCs, such as ONVIF, Hikvision, etc.

Remote control via Web Client or CMS: preview, playback, backup, PTZ and configuration

Support 16CH PoE IPC direct connection to NVR via PoE ports

Multi-user online simultaneously

Authorization management, log view and device status view

4K output, true high-resolution display

Support PTZ preset and auto cruise, up to 255 presets and 8 cruises

Support NAT function and QRCode scanning by mobile phones

Powerful mobile surveillance by smart phones with iOS and Android OS

**Specifications:**

Model		LDSNVR6432-P16-A2
System	OS	Embedded Linux
	Compression	H. 265S/ H. 265+/ H. 265/ H. 264
	IP Video Input	32CH IPC input
	Resolution	12MP/8MP/6MP/5MP/4MP/3MP/ 1080P/ 1
	Network Bandwidth	192Mbps/ 192Mbps (incoming/outgoing)
		HDMI1 : 3840 × 2160/ 1920 × 1080 / 1280 × 1024 / 1
		HDMI2 : 1920 × 1080 / 1280 × 1024 / 1
Video		VGA × 1 : 1920 × 1080 / 1280 × 1024 / 1
	Output	VGA and HDMI1 output the same video s
	Network Input	32 CH IPC audio input
	2-way Audio	RCA × 1
	Local Output	RCA × 1
Audio	Compression	G. 711 (U/A)
	Record Stream	Dual stream recording
	Resolution	12MP/8MP/6MP/5MP/4MP/3MP/ 1080P/ 1
Record	Frame Rate	NTSC: 30fps; PAL: 25fps
	Simultaneous Playback	Max 16CH
	Search	Time slice / time / event / tag / smar
	Smart Search	Highlighted color to display the ca to different record events
Playback	Function	Play, pause, FF, FB, digital zoom, e
Decoding Capability	Live View/ Playback	1CH 12MP/4CH 1080P
		Dual output mode (default mode): sup
	Mode	AI mode : HDMI2 output and 12MP video
Multi-Screen Display Mode	Dual Output Mode	32CH (HDMI1) +4CH (HDMI2)

	AI Mode	24CH (HDMI1)
	Mode	Manual, sensor, motion, exception,
	Input	16 CH local alarm input
	Output	4 CH
Alarm	Triggering	Record, snap, preset, e-mail, etc.

### Rear Panels:

LDSNVR6432-P16-A2

