

# TITANIUM 8CH PoE NVR 8MP/6MP/5MP/4MP/3MP/1080P/720P HD PoE NVR

Model: LDSNVR6108G-P8-V2



## Features:

- Support 8 CH 8MP/6MP/5MP/4MP/3MP/1080P/1280×1024/960P/720P/ 960H/DI/CIF IP video input
- Adopt standard H.265 and H.264 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphic User Interface ( GUI ), Windows style operation by mouse
- Multi-mode recording: manual / timed / motion / sensor / POS / AI recording
- Playback : 4 /8CH simultaneous playback
- Search : time slice, time, event, tag, smart search
- Support multiple VCA (Video Content Analytics) events , such as object abandoned/missing , region intrusion , tripwire , video exception, etc.
- Support POS information overlay on live view and playback
- Express and flexible backup via USB, network and so on
- Pentaplex : preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol
- Remote control via Web or CMS : preview, playback, backup, PTZ and configuration
- 4/8 PoE network ports; IPC can be directly connected to NVR; PoE power supply supported
- Dual stream technology for local storage with high definition , remote network transmission and remote surveillance with mobile device
- Multi-user online simultaneously
- Authorization management, log view and device status view
- 4K output, true high resolution display
- Support NAT function and QRCode scanning by mobile phones

- Powerful mobile surveillance by smart phones with iOS and Android OS

## Specifications:

Model		LDSNVR6108G-P8-V2
System	OS	Embedded Linux
Video	Network Input	8CH IPC input
	Network Input Resolution	8MP/6MP/5MP/4MP/3MP/ 1080P/ 1280 × 1024/960P/720P/960H/D1/CIF
	Output	HDMI × 1 : 3840 × 2160 / 1920 × 1080 / 1280 × 1024/ 1024 × 768 VGA: 1920 × 1080 / 1280 × 1024/ 1024 × 768
	Compression	Standard H.265 / H.264
Audio	Network Input	8 CH IPC audio input
	2-way Audio	RCA × 1
	Local Output	RCA × 1
	Compression	G.711(U/A)
Record	Record Stream	Dual stream recording
	Resolution	8MP/6MP/5MP/4MP/3MP/ 1080P/ 1280 × 1024/960P/720P/960H/D1/CIF
	Frame Rate	NTSC:30fps; PAL:25fps
Playback	Simultaneous Playback	Max. 8 CH
	Search	Time slice / time / event / tag / smart search
	Smart Search	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events
	Function	Play, pause, FF, FB, digital zoom, etc .
Decoding Capability	Live View/ Playback	1CH 8MP; 4CH 1080P
Alarm	Mode	Manual , sensor, motion , exception , smart events
	Input	Supports IPC alarm input
	Output	Supports IPC alarm output
	Triggering	Record, snap, preset, e-mail, etc .
Network	Interface	RJ 45 × 1 ( 10/100/1000Mbps)
	Protocol	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP, HTTP, HTTPS, 802.1x, ONVIF, etc .
	Incoming/ Outgoing Bandwidth	80/80 (Mbps)

	Client Connection	Max. 10 users access
Mobile Device	OS	iOS, Andriod
Storage	HDD Interface	SATA3.0 × 1, max 8T
Backup	Local Backup	U disk, USB mobile HDD
	Network Backup	Yes
Port	USB	USB 2.0 × 2
	Remote Controller	Optional
PoE	PoE Ports	100M RJ45 × 8
	Standards	IEEE802.3af
	Output Power	≤ 96W
Others	Power Supply	DC 48V/2.5A
	Consumption	≤ 10W ( without HDD )
	Dimensions (mm)	300 × 249 × 45( W × D × H )
	Working Environment	- 10 -50 °C 10% - 90% humidity
	Certificate	CE, FCC
	Environmental Protection	Complies with Directive EU RoHS, REACH and WEEE

## Rear Panels:

LDSNVR6108G-P8-V2

